



US012099942B2

(12) **United States Patent**
Geislinger et al.

(10) **Patent No.:** **US 12,099,942 B2**

(45) **Date of Patent:** **Sep. 24, 2024**

(54) **CHEMICAL IMPACTS ON A LEACH STOCKPILE**

(58) **Field of Classification Search**

None
See application file for complete search history.

(71) Applicant: **FREEMPORT MINERALS CORPORATION**, Phoenix, AZ (US)

(56) **References Cited**

(72) Inventors: **Dana Geislinger**, Chandler, AZ (US); **Travis Gaddie**, Phoenix, AZ (US); **Margaret Alden Tinsley**, Titusville, FL (US); **Steven Chad Richardson**, Thatcher, AZ (US); **Raquel Crossman**, Mesa, AZ (US); **Cristian Caro**, Tucson, AZ (US); **Kevin Cheng**, Phoenix, AZ (US); **Rosemary D. Blosser**, Tucson, AZ (US); **Amelia Briggs**, Mesa, AZ (US)

U.S. PATENT DOCUMENTS

6,319,389 B1 * 11/2001 Fountain C22B 15/0002 75/731

8,986,423 B2 3/2015 Lang et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2573936 5/2010
WO WO-2009146485 A1 * 12/2009 C22B 23/0415
(Continued)

(73) Assignee: **FREEMPORT MINERALS CORPORATION**, Phoenix, AZ (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

SW Branch et al. (Acid Generation Prediction in Mining), US Environmental, 1993. (Year: 1993).
(Continued)

(21) Appl. No.: **18/485,143**

Primary Examiner — Hafiz A Kassim

(22) Filed: **Oct. 11, 2023**

(74) *Attorney, Agent, or Firm* — SNELL & WILMER L.L.P.

(65) **Prior Publication Data**

US 2024/0037462 A1 Feb. 1, 2024

Related U.S. Application Data

(63) Continuation-in-part of application No. 18/306,534, filed on Apr. 25, 2023, now Pat. No. 11,893,519, (Continued)

(57) **ABSTRACT**

The system may include a secondary irrigation feature that determines a percent of overlap of each of a plurality of submodules in a first lift over each of a plurality of submodules in a second lift and adjusts at least one of leaching operations or a leaching model based on the total tonnage weighted average of metal in the second lift. The method may further comprise determining an acid gap based on a difference between total acid given and total acid consumption; and further adjusting at least one of the leaching operations or the leaching model based on the acid gap. The method may further comprise determining a percentage of compacted material based on the material that is compacted and irrigated divided by the material that is irrigated; and further adjusting at least one of the leaching operations or

(51) **Int. Cl.**
G06Q 10/00 (2023.01)
C22B 3/06 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **G06Q 10/04** (2013.01); **C22B 3/06** (2013.01); **C22B 15/0067** (2013.01);

(Continued)

(Continued)

