



US012128419B2

(12) **United States Patent**
Coray

(10) **Patent No.:** **US 12,128,419 B2**
(45) **Date of Patent:** **Oct. 29, 2024**

(54) **SYSTEMS, DEVICES AND METHODS FOR IMPROVED EFFICIENCY OF BALL MILLS**

(71) Applicant: **FREEMPORT MINERALS CORPORATION**, Phoenix, AZ (US)

(72) Inventor: **Dale Coray**, Pender Island (CA)

(73) Assignee: **FREEMPORT MINERALS CORPORATION**, Phoenix, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/476,951**

(22) Filed: **Sep. 28, 2023**

(65) **Prior Publication Data**
US 2024/0024884 A1 Jan. 25, 2024

Related U.S. Application Data

(62) Division of application No. 17/574,971, filed on Jan. 13, 2022, now Pat. No. 11,772,101.

(51) **Int. Cl.**
B02C 17/22 (2006.01)
B02C 17/10 (2006.01)
B02C 17/18 (2006.01)

(52) **U.S. Cl.**
CPC **B02C 17/22** (2013.01); **B02C 17/183** (2013.01)

(58) **Field of Classification Search**
CPC B02C 17/22; B02C 17/183; B02C 17/10
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,275,184 A	8/1918	Fairchild	
1,370,699 A *	3/1921	Mitchell	B02C 17/22 241/70
1,590,655 A	6/1926	Spicer	
1,975,501 A	10/1934	Carman	
1,985,801 A	12/1934	Sheehan	
2,893,650 A *	7/1959	MacLean	B02C 17/22 241/70
3,269,668 A	8/1966	Hall	
3,604,637 A *	9/1971	Sabaski	B02C 17/22 241/70
11,772,101 B2	10/2023	Coray	

(Continued)

FOREIGN PATENT DOCUMENTS

GB 461726 2/1937

OTHER PUBLICATIONS

USPTO Non-Final Office Action from U.S. Appl. No. 17/574,971 dated Mar. 31, 2023.

(Continued)

Primary Examiner — Mohammed S. Alawadi
(74) *Attorney, Agent, or Firm* — SNELL & WILMER L.L.P.

(57) **ABSTRACT**

A drum assembly for a ball mill system may comprise: a drum having a first flange extending axially forward from a first radial wall, a second flange extending axially aft from a second radial wall, and a cylinder shell extending axially from a first radially outer end of the first radial wall to a second radially outer end of the second radial wall; a frame coupled to the first flange; and an inlet liner coupled to the frame, the inlet liner comprising a plurality of inlet segments disposed circumferentially adjacent to each other, the inlet liner defining an inlet radius for the drum assembly.

15 Claims, 11 Drawing Sheets

