

- [54] **ESSENTIALLY LINEAR POLYMER HAVING A PLURALITY OF AMIDE, IMIDE AND ESTER GROUPS THEREIN, A TINNABLE AND SOLDERABLE MAGNET WIRE, AND A METHOD OF MAKING THE SAME**
- [75] Inventors: **Donald J. Barta, Ossian; George H. Sollner, New Haven, both of Ind.**
- [73] Assignee: **Phelps Dodge Industries, Inc., New York, N.Y.**
- [21] Appl. No.: **847,263**
- [22] Filed: **Apr. 2, 1986**

Related U.S. Application Data

- [63] Continuation of Ser. No. 481,756, Apr. 4, 1983, Pat. No. 4,611,050.
- [51] Int. Cl.⁴ **B32B 15/00; H01B 7/00**
- [52] U.S. Cl. **428/379; 174/110 N; 174/110 PM; 428/375; 428/473.5; 428/474.4**
- [58] Field of Search **428/375, 379, 458, 383, 428/473.5, 474.4; 528/289, 296, 303; 174/110 N, 110 SR, 110 PM**

References Cited

U.S. PATENT DOCUMENTS

- 3,793,250 2/1974 Schmidt et al. 528/274
- 3,917,892 11/1975 Kawaguchi et al. 428/379 X
- 3,922,465 11/1975 Kawaguchi et al. 428/383
- 4,115,342 9/1978 Shelby et al. 428/379 X
- 4,141,886 2/1979 Sollner et al. 428/458 X

4,319,006 3/1982 Yamada et al. 428/379 X

Primary Examiner—Lorraine T. Kendell
Attorney, Agent, or Firm—Lundy and Walker

[57] **ABSTRACT**

An essentially linear resin having a plurality of amide, imide and ester groups therein comprising the condensation product of at least one polycarboxylic acid five member ring-forming reactant, at least one ethylenically unsaturated polycarboxylic acid five or six member ring lactam-forming reactant, at least one polyfunctional hydroxy compound, at least one difunctional amino five or six member ring forming reactant, at least one polycarboxylic acid reactant having no more than two carboxylic acid ester forming radicals, and at least one polycarboxylic acid reactant having two or more carboxylic acid ester forming radicals with at least two of the radicals in the 1,2 position relative to each other. The method of forming a solution of a prepolymer having a plurality of amide, imide and ester groups therein in cresylic acid or glycol ether solvents and reacting the same with at least one ethylenically unsaturated polycarboxylic acid five or six member ring forming reactant at elevated temperatures. A tinnable and solderable magnet wire having a thin, flexible, tough, thermally stable continuous coating on a conductor which also has a high degree of thermolability (removability in a solder bath) in a solder bath.

15 Claims, No Drawings