



US006890371B2

(12) **United States Patent**  
Marsden et al.

(10) **Patent No.:** US **6,890,371 B2**  
(45) **Date of Patent:** \***May 10, 2005**

(54) **METHOD FOR PROCESSING ELEMENTAL SULFUR-BEARING MATERIALS USING HIGH TEMPERATURE PRESSURE LEACHING**

(75) Inventors: **John O. Marsden**, Phoenix, AZ (US); **Robert E. Brewer**, Safford, AZ (US); **Joanna M. Robertson**, Thatcher, AZ (US); **Wayne W. Hazen**, Lakewood, CO (US); **Philip Thompson**, West Valley City, UT (US); **David R. Baughman**, Golden, CO (US)

(73) Assignee: **Phelps Dodge Corporation**, Phoenix, AZ (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/328,633**

(22) Filed: **Dec. 23, 2002**

(65) **Prior Publication Data**

US 2003/0086849 A1 May 8, 2003

**Related U.S. Application Data**

(63) Continuation of application No. 09/912,945, filed on Jul. 25, 2001, now Pat. No. 6,497,745.

(60) Provisional application No. 60/220,677, filed on Jul. 25, 2000.

(51) **Int. Cl.<sup>7</sup>** ..... **C01B 17/69**; C22B 3/06

(52) **U.S. Cl.** ..... **75/743**; 75/743; 423/522

(58) **Field of Search** ..... 75/743, 744; 423/522

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,605,439 A *	8/1986	Weir	75/744
6,451,088 B1 *	9/2002	Marsden et al.	75/739
6,497,745 B2 *	12/2002	Marsden et al.	75/743
6,626,979 B2 *	9/2003	Marsden et al.	75/739
6,676,909 B2 *	1/2004	Marsden et al.	423/28
6,680,034 B2 *	1/2004	Marsden et al.	423/24

**OTHER PUBLICATIONS**

PCT/US01/23469, International Preliminary Examination Report.

\* cited by examiner

*Primary Examiner*—Melvyn Andrews

(74) *Attorney, Agent, or Firm*—Snell & Wilmer, LLP

(57) **ABSTRACT**

The present invention relates generally to a process for the production of sulfuric acid and liberation of precious metal values from materials containing sulfur through pressure leaching operations. In accordance with various aspects of the present invention, the sulfur-bearing materials may comprise residues from pressure leaching operations, such as those carried out at medium temperatures. The process of the present invention can be advantageously used to convert such sulfur-bearing materials to sulfuric acid by means of pressure leaching. The sulfuric acid so produced can be used beneficially in other mineral processing operations, for example those at the site where it is produced. Metals, such as precious metals, that are contained within the sulfur-bearing materials advantageously may be recovered from processing products by established precious metals recovery technology.

**18 Claims, 2 Drawing Sheets**

