



US007191603B2

(12) **United States Patent**
Taube

(10) **Patent No.:** **US 7,191,603 B2**
(45) **Date of Patent:** **Mar. 20, 2007**

(54) **GASEOUS FLUID PRODUCTION APPARATUS AND METHOD**

(75) Inventor: **Joel A. Taube**, Donnellson, IA (US)

(73) Assignee: **Climax Molybdenum Company**, Phoenix, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/251,043**

(22) Filed: **Oct. 14, 2005**

(65) **Prior Publication Data**

US 2006/0086100 A1 Apr. 27, 2006

Related U.S. Application Data

(60) Provisional application No. 60/619,436, filed on Oct. 15, 2004.

(51) **Int. Cl.**

F17C 9/02 (2006.01)

F17C 7/04 (2006.01)

B65B 3/04 (2006.01)

B65B 1/04 (2006.01)

(52) **U.S. Cl.** **62/50.2**; 62/48.1; 141/231; 141/3

(58) **Field of Classification Search** 62/50.2, 62/48.1, 50.6; 141/231, 3

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 3,804,108 A * 4/1974 Ferrari 137/112
- 4,406,129 A * 9/1983 Mills 62/7
- 4,555,387 A 11/1985 Sabacky et al.
- 4,865,832 A 9/1989 Kamijyo
- 5,045,516 A 9/1991 Vogel et al.
- 5,185,133 A 2/1993 Scheffic et al.
- 5,214,925 A * 6/1993 Hoy et al. 62/50.6

- 5,243,821 A * 9/1993 Schuck et al. 62/50.6
- 5,472,749 A 12/1995 Dravid et al.
- 5,514,350 A 5/1996 Kear et al.
- 5,582,218 A * 12/1996 Beale 141/3
- 5,590,535 A * 1/1997 Rhoades 62/50.2
- 5,665,277 A 9/1997 Johnson et al.
- 5,698,483 A 12/1997 Ong et al.
- 5,762,119 A * 6/1998 Platz et al. 141/231
- 5,788,738 A 8/1998 Pirzada et al.
- 5,804,151 A 9/1998 Sweetser et al.
- 5,820,844 A 10/1998 Khan et al.
- 5,851,507 A 12/1998 Pirzada et al.
- 5,874,684 A 2/1999 Parker et al.

(Continued)

Primary Examiner—William C. Doerrler

(74) *Attorney, Agent, or Firm*—Fennemore Craig, P.C.; Bruce E. Dahl; Susan E. Chetlin

(57) **ABSTRACT**

Gaseous fluid production apparatus according to one embodiment of the invention includes a fluid container containing fluid in substantially the liquid state. A first fluid line is connected to the fluid container so that it receives from the fluid container a first fluid stream substantially in the liquid state. A gas generator is also connected to the fluid container so that it receives from the fluid container a second fluid stream substantially in the liquid state. A product discharge manifold is connected to the gas generator and to the first fluid line. A control means is operatively associated with the first fluid line and the product discharge manifold for controlling at least one parameter of the first fluid stream. A second control means is operatively associated with the gas generator and the product discharge manifold for controlling at least one parameter of the second fluid stream.

4 Claims, 1 Drawing Sheet

