



US007565811B2

(12) **United States Patent**
Taube

(10) **Patent No.:** **US 7,565,811 B2**
(45) **Date of Patent:** **Jul. 28, 2009**

(54) **GASEOUS FLUID PRODUCTION APPARATUS AND METHOD**

(75) Inventor: **Joel A. Taube**, Donnellson, IA (US)

(73) Assignee: **Climax Molybdenum Company**, Phoenix, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 78 days.

(21) Appl. No.: **11/671,738**

(22) Filed: **Feb. 6, 2007**

(65) **Prior Publication Data**

US 2007/0130964 A1 Jun. 14, 2007

Related U.S. Application Data

(63) Continuation of application No. 11/251,043, filed on Oct. 14, 2005, now Pat. No. 7,191,603.

(60) Provisional application No. 60/619,436, filed on Oct. 15, 2004.

(51) **Int. Cl.**

F17C 9/02 (2006.01)
B65B 1/04 (2006.01)
B65B 3/04 (2006.01)

(52) **U.S. Cl.** **62/50.2**; 141/3

(58) **Field of Classification Search** 62/50.2, 62/48.1, 50.6; 141/231, 3
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,001,375	A *	9/1961	Tauscher	62/50.4
3,800,550	A *	4/1974	Delahunty	62/47.1
3,804,108	A	4/1974	Ferrari		
4,127,008	A *	11/1978	Tyree, Jr.	62/62
4,406,129	A	9/1983	Mills		
4,555,387	A	11/1985	Sabacky et al.		
4,865,832	A	9/1989	Kamijyo		

5,045,516	A	9/1991	Vogel et al.		
5,185,133	A	2/1993	Scheftic et al.		
5,214,925	A	6/1993	Hoy et al.		
5,243,821	A	9/1993	Schuck et al.		
5,472,749	A	12/1995	Dravid et al.		
5,514,350	A	5/1996	Kear et al.		
5,572,864	A *	11/1996	Jones	60/220
5,582,218	A	12/1996	Beale		
5,590,535	A *	1/1997	Rhoades	62/50.2
5,665,277	A	9/1997	Johnson et al.		
5,698,483	A	12/1997	Ong et al.		
5,762,119	A	6/1998	Plazt et al.		
5,788,738	A	8/1998	Pirzada et al.		
5,804,151	A	9/1998	Sweetser et al.		

(Continued)

Primary Examiner—William C Doerrler
(74) *Attorney, Agent, or Firm*—Fennemore Craig, P.C.

(57) **ABSTRACT**

Gaseous fluid production apparatus according to one embodiment of the invention includes a fluid container containing fluid substantially in the liquid state. A first fluid line is connected to the fluid container so that it receives from the fluid container a first fluid stream substantially in the liquid state. A gas generator is also connected to the fluid container so that it receives from the fluid container a second fluid stream substantially in the liquid state. A product discharge manifold is connected to the gas generator and to the first fluid line. A controller means is operatively associated with the first fluid line and the product discharge manifold for controlling at least one parameter of the first fluid stream. A second controller means is operatively associated with the gas generator and the product discharge manifold for controlling at least one parameter of the second fluid stream.

17 Claims, 1 Drawing Sheet

